



Multifunctional dynamic TFT exit sign luminaire made of UV- and glow wire resistant polycarbonate. For indication of the safe escape route in variable directions and blocking of affected areas depending on the spread of smoke from a fire as well as display of various safety signs or customer-specific pictograms. With the TFT used, including backlight and image content monitoring, the pictograms are displayed in accordance with standards and can be easily exchanged.

#### Technical data

<b>Viewing distance:</b>	20 m
<b>Material:</b>	Polycarbonate
<b>Illuminant:</b>	TFT
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	69 mA

<b>Nominal current DC:</b>	40 mA
<b>Apparent power:</b>	15,8 VA
<b>Effective power:</b>	9,9 W
<b>Protection class:</b>	II
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C

**Available colours** Add colour code to the article no. e.g. 800 014 **LXX**

Special colour: **L99**


#### Articles

##### FL 2820 D TFT FDC 230V

Art. no. 811 184

Ceiling mounting

Protection category: IP40



##### FL 2820 TFT FDC 230V

Art. no. 811 180

Recessed- and wall mounting

Protection category: IP40

